



Nonmetallic Liquid Tight Conduit - Type 'B'

Flexible PVC - Gray-

Features

- Resists corrosion, abrasion, oil, water, acid and rough environments.
- For direct burial and poured concrete
- Outdoor, sunlight resistant
- Can be installed with either nonmetallic, cast zinc or metal liquid tight connectors
- Temperature Range: -18°C to 80°C dry, 60°C wet, 75°C oil
- IP68 Rating - use Nesco PXXX series straight & 90° connectors

Applications

- Suitable for indoor or outdoor use
- Applications rated to 600V
- Quick installation, cuts with a utility knife or PVC cutter

Standard Material

- Integral Rigid and flexible PVC construction

Certification

- UL File #: E494632



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/ Case	Outside Diameter		Inside Diameter		Wall thickness
						Min.	Max.	Min.	Max.	
15004	11350	3/8"	---	100'	10	0.69	0.71	0.484	0.504	0.21
15005	11351	1/2"	---	100'	13	0.82	0.84	0.622	0.642	0.21
15007	11353	3/4"	---	100'	18	1.03	1.05	0.82	0.84	0.21
15008	11355	1"	---	100'	25	1.29	1.315	1.041	1.066	0.25
15009	11356	1-1/4"	---	100'	33	1.63	1.66	1.38	1.41	0.25
15010	13344	1-1/2"	---	50'	23	1.865	1.90	1.575	1.60	0.30
15011	15762	2"	---	50'	30	2.34	2.375	2.02	2.045	0.33

Nesco Inc.

1039 Cardiff Blvd., Mississauga, ON L5S 1P4

TF: (866) 466-3726 Tel: (905) 793-2218 Fax: (905) 793-2268

www.nescocanada.com

Ref. 1